

M

THE PROPERTY BLUFASE, PLANTER WITHOUT WITHOUT BY

64 183 73 10 182

METADROLOGICAL DATA REPORT

183088 MLRS 846416 Manber 35-111-86-110-86-108-86-105-86-103-86-102 183088 Manber 1-889/79-29 thru V-294/P0-34 285-0015 1982

> DANALE : SELLER Propries Suppor Leave its for Phone Businer (SCE) 575 9568 AND Suppor SASJUSSES

A CONTROL OF THE PARTY OF THE PARTY.

The state of the s


UNCLASSIFIED
SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered)

REPORT DOCUMENTATION	PAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM		
1. REPORT NUMBER	2. GOVT ACCESSION NO.			
DR 1251	AD- A119069			
4. TITLE (and Subtitle)	<u> </u>	5. TYPE OF REPORT & PERIOD COVERED		
19308B MLRS				
Missile Number BC-111,BC-110,BC-1	08,BC-105,BC-103			
BC-102		6. PERFORMING ORG. REPORT NUMBER		
Round Number V-289/PQ-29 thru V-2	94/PQ-34 ·	8. CONTRACT OR GRANT NUMBER(s)		
7. AUTHOR(S)		6. CONTRACT OR GRANT NUMBER(#)		
White Sands Meteorological Team		DA Task 1F665702D127-02		
9. PERFORMING ORGANIZATION NAME AND ADDRESS	<u> </u>	10. PROGRAM ELEMENT. PROJECT, TASK AREA & WORK UNIT NUMBERS		
ſ		ANEX & WORK DRIT HOMBERS		
j				
11. CONTROLLING OFFICE NAME AND ADDRESS		13		
US Army Electronics Research and	Development Cmd	12. REPORT DATE 23 July 1982		
Atmospheric Sciences Laboratory	•	13. NUMBER OF PAGES		
White Sands Missile Range, New Me	xico 88002	41		
14. MONITORING AGENCY NAME & ADDRESS(II dittorer	nt from Controlling Office)	15. SECURITY CLASS. (of this report)		
US Army Electronics Research and	Development Cmd			
Adelphi, MD 20783		UNCLASSIFIED		
•		15. DECLASSIFICATION DOWNGRADING SCHEDULE		
16. DISTRIBUTION STATEMENT (of this Report)				
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report) Approved for public release; distribution unlimited.				
18. SUPPLEMENTARY NOTES				
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)				
Meteorological data gathered for t Number BC-111,BC-110,BC-108,BC-105 thru V-294/PQ-34 are presented in	he launching of BC-103, and BC-	the 19308B MLRS, Missile 102, Round Number V-289/PQ-29		

5	ECURITY CLASSIFICATION OF THIS PAGE(When Date Entered)	٦.
l		İ
		I
ı		I
ı		
Ì		
I		1
ı		l
١		Ì
l		١
l		١
ĺ		I
ı		ł
l		١
l		
		I
Ì		١
l		Ì
l		
		I
l		Į
l		İ
l		١
l		I
		l
		l
ĺ		l
l		1
١		l
		1
ı		1

	CONTENTS	PAGE
INTRODUCT	ION	1
DISCUSSION	¥	1
GENERAL A	REA MAP	2
LAUNCH ARI	EA DIAGRAM	3
TABLES		
1.	Surface Observation Taken at 1215 MDT at D-3½	4
2.	Launch and Impact Area pilot-balloon Measured Wind Data	5
3.	Aiming and T-Time Computer Met Messages	6
4.	NW-30 Significant Level Data at 0800 MDT	8
5.	NW-30 Upper Air Data at 0800 MDT	10
6.	NW-30 Mandatory Levels at 0800 MDT	15
7.	E-28 Significant Level Data at 0900 MDT	16
.3	E-28 Upper Air Data at 0900 MDT	18
9.	E-28 Mandatory Levels at 0900 MDT	· 22
10.	NW-30 Significant Level Data at 1100 MDT	· 23
11.	NW-30 Upper Air Data at 1100 MDT	· 25
12.	NW-30 Mandatory Levels at 1100 MDT	30
13.	E-28 Significant Level Data at 1215 MDT	· 31
14.	E-28 Upper Air Data at 1215 MDT	. 33
15.	E-28 Mandatory Levels at 1215 MDT	· 37





INTRODUCTION

19308B MLRS, Missile Numbers BC-111, BC-110, BC-108, BC-105, BC-103, and BC-102, Round Numbers v-289/PQ-29 thru V-294/PQ-34, were launched from Brillo, White Sands Missile Range (WSMR), New Mexico, at 1215:01, 1215:06, 1215:10, 1215:15, 1215:19, and 1215:24 MDT, 23 July 1982. The scheduled launch times were 1200, 1200:04.5, 1200:09, 1200:13.5, 1200:18, and 1200:22.5 MDT.

Meteorological data were recorded and reduced by the White Sands Meteorological Team, Atmospheric Sciences Laboratory (ASL), White Sands Missile Range, New Mexico. The data were obtained by the following methods:

1. Observations

- a Surface
- (1) Standard surface observations to include pressure, temperature (O C), relative humidity, dew point (O C), density (gm/m 3), wind direction and speed, and cloud cover were made at the D-3½ Met Site at T-0 minutes.
- (2) Monitor of wind speed and direction from one anemometer was provided in the launch control room.
 - b. Upper Air
- (1) Low level wind data were obtained from pilot-balloon observations at:

SITE AND ALTITUDE


D-3½ 2 km MAL 2 km


(2) Air structure data (rawinsonde) were collected at the following Met Site:

SITE AND TIME

NW-30	0080	MDT
E-28	0900	MDT
NW-30	1100	MDT
E-28	1215	MDT

WSMR METEOROLOGICAL SITES





PROJECT SURFACE OBSERVATION

DATE 23 July PEAR 82 * 441,121.6 Y= 387,107.8 H= 4005.2 TIME PRESSURE of mbs TEMPERATURE of OF OC OF OC OF OC OF OC OF OC OF OC OC OC OC OC OC OC OC OC OC OC OC OC	TABLE								STATION D 312			
RESSURE TEMPERATURE DEW POINT HUMIDITY DEWSIJY albs of of OF 29 990	DATE 23		V 82	ŀ				<i>(</i> *)	= 441,121.6	γ= 3	8Z 10Z 8 H	4005.2
881.1 34.4 13.6 29 990 140 07	11 ME	PRESSURE mbs	TEI PER	4TURE OC	DEW P(Jont Oc	PELATIVE HUMIDITY %	DEMSIIY ga/m³		WIND SPEED Kts	CHAPACTER kts	VISIBIL- ITY
	1215	881.1		34.4		13.6	. 62	066	140	70		40
							•					

				J	Tollos					
STRUCTIONS	35	t LAYE	جد	2nc	LAYE	Ć	1 3r	d LAYE	وا	REMARKS
TO VISIBILITY AMT TYPE HGT	AMT	TYPE	1 HGT	AMT	AMT TYPE HGT	HGT	A:T	APT TYPE HGT	HGT	
NONE	ی	30 6000	6000							
							ļ			

 TIME:
 MDT
 1215

 DRY GULB TEMP.
 34.4

 WET BULB TEMP.
 20.2

 WET BULB DEMP.
 14.2

 DEW POINT
 13.6

 RELATIVE HUMID.
 29

23 July 1982

13: D-31 ₂ 11: 1215 MDT	MAL 1219 MDT
grammer of 100 days	
441,053.12	509.421.05
386,316.94	495,563.18
4,008.31	4,126.80

taring the 1V	11/12/11/11 61/07/11/2	er ort. Profis	1979 (1911) 11 11 11 11 11 11 11 11 11 11 11 11 11		
	140	07	9.000	190	04
	100	04	1:5	077	04
	097	04		067	05
	111	05	4 - 0 - e 1 - e	063	05
	121	06	7:1	057	04
	125	06		050	03
	130	06	1000	013	02
• 1/2	120	80	r	351	01
	113	10		314	01
$\epsilon_{\epsilon_{i+1}^{*}}$	091	08	96	010	02
	091	07	170	037	05
,	084	12	1400	018	03
150	084	14	$\sum_{k=1}^{n} I_{k-1}$	242	02
	086	16	175.1	180	04
	091	15	233	144	05

All data obtained from single Theodolite Tracked pilot-balloon observations.

AIMING AND T-TIME COMPUTER MET MESSAGES 23 July 1982

NH-30 080	TOM OC	E-28 0900 MDT
METCM1329	065	METCM1329064
2314001228	384	231500119886
00160001	30010884	00124002 29990886
01277004	29940873	01197005 29970876
02293009	29770849	02242005 29780851
03245012	29470811	03133007 29580813
04097011	29080765	04142011 29230767
05134012	28690721	05143014 28760723
06123017	28270679	06137016 28360681
07111018	27810639	07146016 27990641
08128018	27450601	08166017 27610603
09153019	27090564	09164013 27240567
10154013	26800530	10148012 26860532
11140011	26530497	11143013 26510499
12151014	25980451	12209011 26040453
13170027	25310395	13189024 25280397
14188028	24840345	14189030 24790346
15201018	24230300	15187022 24270301
16121012	23460260	16152019 23580261
17122025	22700225	17134019 22870226
18149024	22070193	18129020 22170194
19154022	21340165	19161028 21480166
20160033	20650140	20184042 20780142
21174035	20360119	21193040 20310120
22179029	20580101	22186030 20440102
23191023	20790085	23187027 20670086
24201025	20920073	24213027 21110073
25191022	21290062	25203022 21300062
26159040	21990053	26157034 21940053

AIMING AND T-TIME COMPUTER MET MESSAGES 23 July 1982

301.20 11	OO MOT	C 20 121	E MOT
NW-30 11		E-28 121	
METCM1329		METCM1329	
231700122		231830119	
00320003	30680883	00000000	30700085
01196009	30360873	01325003	30510875
02213004	30100849	02311006	30210851
03212004	29710811	03267005	29840813
04187004	29230765	04229009	29400768
05235006	28780722	05196012	28970724
06203011	28390680	06198018	28530682
07205013	28030640	07221021	28130643
08203011	27620602	08238014	27710604
09207013	27200566	09224011	27250568
10181016	26850531	10175016	26920534
11175013	26550498	11182015	26650501
12180018	26090452	12179017	26150454
13227024	25540396	13240021	25620398
14216022	24960346	14215025	25030348
15192023	24270302	15196034	24310303
16191026	23510262	16212025	23550263
17153023	22870226	17170025	22930227
18159028	22260194	18171032	22350196
19176036	21510166	19197039	21640168
20206037	20780142	20214038	20910143
21202034	20300120	21199032	20320121
22183027	20470102	22197029	20580103
23195029	20760086	23198025	20800087
24215020	21270073	24203025	21230074
	21470063	25206023	
26170032		26165030	
	-		

	SIGNI
STATION ALTITUDE 4010,40 FEET MSE	
8.2 0800 110T	
2	. V +
•	34-

DATA		
SIGNIFICANT LEVEL	0.000 S	بال

GEODETIC COORDINATES 37.86457 LAT DEG 106.49714 LON DEG

G.	LSSURE	GEOMETRIC	TEMPERA	ATURE	REL.HUM.
		LTITUD	<u>م</u>	HPOINT	ERCEN
MIL	LIBARS	St FEE	REFS C	NTIGR	
œ	, S	010	,	11.7	,
) ex	200	127			
, ~	200	00.0	. <		ċ
. ~	0.00	0.565	•	•	: .
•	63.1	2039.	9	•	6
•	19.8	3848	1.9	7.4-	64.0
9	14.2	4089	•	တ	3:
•	85.4	5358.	•	13.	
i.	56.8	6668.	•	;	-
\$	00°00	9443.	2	27.	
*	7.07	*526C		6	Ġ.
4	39.4	2706.	-15.1	29.	ů
4	32.8	3381	•	26.	ij
•	26.8	7427	17.	34.	Š
4	20.4	1799.	2	31.	8
4	0.80	4536.	18.	₹0.	ċ
4	0.00	5320.	٠ 0	17.	ċ
m	89.6	5660.	.1.3	τ 8	ċ
* ^	76.0	6523	-	æ ∞	ċ
r	9. 99	7269.	22.	40	8
•	54.8	7326.	23.	41.	
M	11.7	1010.	28.	44.	•
••	D. 00	1908	.1.	-47.5	•
r:	81.5	3352.	7.	6.0	•
~	50.0	6082.	ô		
~	03.9	r553.	50.		
~	0.00	0967	50.		
-	52.5	6626.	63.		
_	20.0	6966.	54.		
•	35.3	9322.	68.		
-	23.5	.998	40.		
-	14.2	2358.	68.		
-	68.7	*333.	69		
_	8.90	3680.	69.		
-	30.0	49R1.	67.		
	2.1	6672.	. 79		
	3.6	P.87C.	•		
	3.07	62157.1	63.		
	۳. •	420			
		7.71	S		
	<u>.</u>	•			

STATION ALTITUDE 4716,40 FFET MSL 23 JULY 82 0300 HDT ASCENSION NO. 20

SIGNIFICANT LEVEL DATA
2047220029
Nw 3C
TABLE-4 cont'd

GEODETIC COORDINATES 32.88497 LAT DEG 106.49714 LON DEG

TEMPERATURE AIR DEWPOINT DEGREES CENTIGRADE

PRESSURF GEOMETRIC ALTITUDE MILLIBARS MSL FEET

69163.4 78901.7 80084.2 84070.0 86793.7 89008.2 255.0 255.0 255.0 255.0 155.0

REL.HUM. Percent

TATION A	TITUDE 4	710.40 FEET	ET MSL	_	AIR 32200	DATA 20		I	C COORDINATE
23 JULY 82 ASCENSION	NO. 2C	101 008r		~	NE 30 TABLE-5			32. 106.	88497 LAT DEG 49714 LON DEG
GEOMETRIC	PRESSURE	1 53	PERATURE	E.	DENSITY	SPEED OF	AIND DA	4	INDEX
LTITUBE		18	DEWPO	PERCENT	GM/CUBIC	SOUND	IRECTION	SPEE	0
w	MILLIBARS	œ	CENT16R		ETE	KNOTS	REES (2	REFRACTION
010	83.	5	÷	43.0	25.	74.	€.	•	.00028
530.	68.			å	=	73.	44.	•	0028
500	53.	'n	•	2	97.	72.	51.	•	.0003
500.	38	۶.	•	'n	84.	7.	5.1.	ċ	0027
000	24.	:	•	;	70.	70.	47.	•	•00056
500	809.7	0.0	O .	9	57.		,	-	00026
000	92.	en en	•		, 4.	67.	13.	•	.00025
200	61		•	œ i	31.	99	œ.	•	0025
9	67.	•	•	ů	49	64.	,	•	•00054
900	•	.	•	'n	90	5	٠,	. .	72000
000	9	•	•	•	93	5	,	•,	*2000*
200	27	m	•	ů	91	60	ائن	•	00023
000	•	- 1	•	٠,	60	20	٠, ۱	•	.2000
500	5	•	•	•	57.	57.	٠,١	•	£2000*
		•	•		6 2		. · r	•	27000
200	ė:	•	•	•	* 1		٠,	•	>>0000
	• • •	•	0.0	7.6.7	53		'n,	•	2200
	•	7.	•	•	•	• •	٠,	•	12000.
900	• •	•	i.	ġ,	5 8	•	٠.	•	27000
9 6	• • •	•	;,	å,		. a	٠ •	٠,	02000
	• ·	•	ů	•	• •	0 7		•	
	• ·	•	• • • • •	•	2 2	. 7 4	• <		
500	· 00			7.7.		4	, -	•	00017
000	71.	0-1-	14.		32	42.	•		.00017
6500.	60	m	•		2.5	60	÷	•	00017
7000°	4	•	•	æ	٠ <u>.</u>	39	. •	•	.00016
7500.	39.		•	•	66	8		•	.00016
÷000°	28.	•	•	ċ	67.	17.	ţ	•	00016
8500.	18.	÷	•	÷	76.	9		2	.0001
•0005	0	~	•	2	65.	3	•	•	.00015
9500	98.	7.7-	.•	\$	54.	34.	ů	ċ	0014
300C	89.	8	•	•	44.	33.		•	0014
0050	79.	ċ	•		34.	. 7.	ŗ.	•	0014
1000	70.	ç		•	. 77	-	•	•	.00014
1500.	61	12.			14.	29.			2017
<u>2000</u>	:	•	•	÷	S	28.	۲.	;	.0001
.0053	43.	14.	-26.1	ق	٠ ٧ ٥	26.		•	0017
23000.0	474.2	15.9	7-92-	60 I	587.6	625.1	9 00	7 00 0	1.000175
3500.	25.	17.		٠,	78.	33	•	•	2001

MSL	
TATION ALTITUDE 4010.40 FEET 3 JULY 82	•
ALTITUDE 82	(a
TATION	Trans.

UPPER AIR DATA 2040220020 NW 30 TABLE-5 cont'd

6E0DETIC COORDINATES 32.88497 LAT DEG 106.49714 LON DEG

a former or represented to the artificial continues.

a to accept of the table of the control of the cont

INDEX Of Fraction	1.030129		0012	0012	.00012	=	Ξ	.00011	00011	.0001	.00010	.00010	.00010	.00010	.00010	•	ě	60000*	6000	00000	6000	.0000	900	00000	0000	0000	00000	0000	000	•0000	000	000	0007	1.0000.1	1.00001	9	0000	1.000066	9000	
A Speed Knots Re	-	2		7	÷	3.	8	•	ċ	28.5	•	•	2	:	ċ	•	÷	3.	•	ċ	•	•	۶.	ņ	•		ċ	-	3.	Š	÷	•	÷	÷	.,	;	~	ວໍ	~	
WIND DAT DIRECTION DEGREES(TN)	8 0	2	,	9			-		ř	104.0	š	۲.	•	۴.	ď	š	;	÷	ċ	è	•	÷	2	÷	D• 29	•	•	Ö	•	÷	·	•	.;	÷	٠,	•	•	,•	0	٠
PEED OF SOUND KNOTS	22.	21.	19.	18	18.	2	2	2	5	614.1	2	12	Ξ	5	S	2	8	2	8	5	8	80	6	5	8	2	6	0	œ •	•	~	8	2	2	-	79	28	76	7.5	1
DENSITY S GM/CUBIC METER	89	~	51.	42.	31.	~	11.	~	94.	485.6	77.	68.	60.	2	44.	37.	30.	23.	15.	90	32.	95.	68.	82.	÷	60	62	56.	50.	6.3	37.	31.	25.	<u>:</u>	ζ.	90	-	9.6	Ċ	7 3
REL.HUM. PERCENT		Ġ	ċ		6	•	8	8	8	18.2	÷	8	å	÷	ċ	å	÷	8	æ	6.0*	4.		*2	-	*															
ERATURE Dewpoint Centigrade	2		2			80	ċ	0	-41.4	-42.0	-42.5	-43.1	-43.7		6.44-	•	-47.6	-48.3	0.67-	ċ	ň	÷	ö	0.99-	ċ															
TEMP AIR Degrees		-18.6	-20.1	-	-	*	-	-22.8	m	-24.7	-25.5	-26.2	-27.0	-27.8	-28.6	-30.0	-31.3	-32.3	-33.4	5.7.	S	~	-38.2	39	9	-	-42.9	•		-46.3	_	-48.5	•	ċ	ċ	-	-52.9	•	5	•
PRESSURE MILLIBARS	17.		90	32.	84.	76.	68.	61.	53.	346.4	39.	32.	25.	18.	=	5.	98.	.20	86.	90.	74.	68.	62.	56.	20	£ 2•	6 M	34.	29.	23.	8	13.	60	04.	66	95.	ပံ	w\	-	
· GEOMETRIC ALTITUDE MSL FEET	4000	4500.	5000.	5500.	6000	6500.	7000	7500.	5000.	28500.0	9000	9500.	0000	C500.	1000	1500.	20003	2500.	3000	3500.	* 000*	4500.	5000.	5500.	6000°	6500.	7000	7500.	£000°	8500.	9000	9500.	0000	C500.	10001	00	.0003	00	00	200

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION AL 23 july 82	TITUDE 4	0800 MOTERT MSL	-	UPPER AIR (204022002 NW 30 TAREES CO	S DATA		GEODETIC 32-8	IC COORDINATES -88697 LAT DEG
16236	•				ت د =			20 100 1100
-	PRESSURE	TEMPERATURE	REL		SPEED OF	WIND DATA	1 A	INDEX
ALTITUBE		AIR DEWPOI	۵	GM/CUBIC	OCN	DIRECTION	PEE	90
	MILLIBARS	DEGREES CENTIGRAD	W.	METER	KNOTS	DEGREES(TN)	KNOTS	REFRACTION
4000	173.0	57.		79.	572.2	~	18.3	900
4500	168.9	8		74.	~	~	-	900
8	•			ćγ	69	86.6	,	000
5500	-			. 79	67	•	7	0000
8	~	62		20	•	1-	ċ	0000
6500	153.4	63		254.5	64.	87.6	-	000
8	0	-64.1		6	563.3	ec	2	00000
7500	•	65.		44.	61.	O		Š
2009	2			3	9	~	÷	3
8500	8	-67.2		34	53	4	2	ä
8	~	8		36.	57	5	1	00002
5500	~	•		25.	56	•	٥.	3
0000	80	69		20.	56	S	Š	0000
6500	5	0		15.	53	;	\$	•0000•
1000	~	-70.3		10.	5.4	8.6	;	0000
1500	0	ŝ		5.	55	4	'n	•0000•
2000	116.3	-69.1		98.	28	W١	32.3	.0000
2500	m	63		93.	57	•	:	• 0000
3000	O	68.		80	56	~	ċ	•0000
3500	~	8		•	56	v	•	ž
4000	~	-69.2		•	28	L	~	Ž
4300	3	-68.1		•	57	ø	2	2
55000.0	6.66	67		168.9	559.3	6. (C	32.2	0000
2500	~ I	99		•	9	•	- (-0000
0009	n	\$		•	9	5	10	.0000°
6500	N 1	•		154.7	2	106.7	2	Ė
2027	200	ő		•	7	•	7	00000
2500		•		٠	70	٠.	-	10000
8000	86. 0	6		•	~	.	-	.0000
8500	•	Ø			65	•	r	5
2030	C	-66.1		•	9	12.	•	b
0055	6.54	65.		•	5	•	26.0	.0000
0000	~	65.		•	5	-	~	.0000
5330	O	-54.8		•	62	111.7	~	6
1000	4				ž	-	∞	7000v
1550	~	v			3	==	۲.	ć
2000	O	*		•	4 3	Ċ.		0000
2500	68.8	53			49	107.4	9	
2000	~	62		-	65	ç	•	50000
3530	65.5	62		10.01	65		•	0000
) -	,	•		•	1			;

STATION ALT: 23 July 82 Ascension Mo	TTUBE 4	016.40 FEET 0800 MDT	J S	<u>م</u> د	UPPER AIR DATA 2740220020 ABLE-5 cont'd	\$414 20 1,q		GEODETIC 32.88	C COORDINATES 88497 LAT DEG 49714 LON DEG
GEOMETRIC Altitude Msl feet	PRESSURE MILLIBARS	TEMPER Air D Degrees Ce	ATURE EMPOINT NTIGRADE	REL.HUM. Percent	DENSITY GM/CUBIC METER	SPEED OF Sound Knots	WIND DA DIRECTION DEGREES(TN)	TA SPEED Knots	INDEX Of Refraction
00	m)	-62.2			٠.	65.	0.5		1.000024
450C.	5	÷.			~	67	3.		2000
2000	•	₩.			•	269.0	10.0	28.3	20000
5500.	6	8			•	20	5		20000
\$00¢	8	20			Ď.	2	۲.	.	20000
6500.	ġ.	-55.5			ė.	7	m e	٠,	1.000020
7000		χ:			E 4	0 1	<u>.</u> .	•	20000
	• •	1000				- 1	• ·	•	
5500	; ;	, ,			•	- ×	4.0	•	0000
9000		25				2 2	,	M	0000
9500.	6	2				2	•		00000
0000	8	25			Š	70	Ø	-	00001
6500.	,	~			÷	2		-	10000
1000	š	25				4	8	0	000
1500.	•	2			ċ	4	v .	ec (0000
2000	'n.	21			٠,	20	•	٠,	0000
• 00 C V	;.	v			٠.	9 0	~ •	D+	
2000	: 6	4075			; ;	2 6	- F	000	1,00001
4000		3				78	œ		0000
4500.	6	~			;	7.8	0		000
5000.	8	5			•	78	•	•	00001
5500.	۴,	25			.	R (m·		00001
	ė,	0.25			٠,	9 9	e v	•	
7000	; ;	,,			•	2 0	٠ ٧		
7500.	'n	2			-	80	ر و د	3	00000
8000	ň	52			6	78	30	~	1000
8500.	i,	32			.	78	PO	-	0000
0003	:	25			ď.	2	5	ċ	0000
9500	ċ	W . 1				0	en .		10000
בנים נינים נינים	.				٠.	- (3 (٠.	10000
20C	• •	* * * * * * * * * * * * * * * * * * *			•	2 6		:,	
1700	• «	7			, ,	7	4	. 0	1000
	,	, ,			•		•		
	. 4	3			•	, ×		,	
7000	. 4	46.				\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	٠	· «	
81500.0	25.7	45			30.3	0.000	51.5		0000

GEODETIC COORDINATES 32.88497 LAT DEG 106.49714 LON DEG	A INDEX Speed of Knots refraction	1.00000	23.2	1.0000	1.00000	1.0000	1.00000	1.00000	_	1.00000	•-	_	_	1.00000	4.00000	1.00000	1.00000	-	-	48.3 1.000006	1.000005	1.000005	1.000005	1.00000\$	1.000005	0000
.	WIND DATA DIRECTION SP DEGREES(TN) KN	ء ب	- •-			7.6							٥.		Š	•	8°06	-	9 ? • 2	92.5						•
0020 cont'd	SPEED OF C SOUND KNOTS	38.2 588.8					587	583										.0 589.0		.9 SBB.4						21.7 590.1
UPPER AIR DATA 2040220020 Nw 30 TABLE-5 contid	DENSITY Gm/cubi meter	100 t	7 10	35	35	40	E M	32	33	31	30	50	53	28	27	22	92	92	25.5	72 .	77	23	53	22	22	.
	REL.HUM. T PERCENT	-							• • •																	
ET #SL	PERATURE Dewpoin Centigra																									
010.40 FEET 0800 HDT	AI DEGR	7.44-	-45.0	-45.3	-45.5	-45.8	-45.6	6.44-	-44.3	-43.6	-42.9	-43.1	-43.4	-43.6	-43.8	-44.1	-44.3	-44.5	8.44-	-45.0	-45.2	-45.5	-45.7	-45.7	-44.7	-43.7
ALTITUBE 40 82 On No. 20	PRESSURE MILLIBARS	25.1	1 4	m	2.	2	÷	- (ċ	ċ	20.0	19.6	19.1	18.7	8	17.9	17.5	17.1	16.7	16.3	16.0	15.6	15.3	14.9	14.6	14.3
STATION AL 23 JULY 82 ASCENSION	GEOMETRIC Altitude MSL FEET	84000.0	2000	85500.0	9009	6500	2000	7500	8000	3500	000	9500	0000	0200	1000	1500	2002	2002	2000	3500	4000	4500	5000	5500	0009	6500

HANDATORY LEVELS 2047220020 TABLE-6
STACION ALTITUDE 4010.40 FEET MSL 23 JULY 82 0800 MDT ASCENSION NO. 20

ORDINATES 7 LAT DEG 4 LON DEG												
GEODETIC CUORDINATES 32.88497 LAT DEG 166.49714 LON DEG	ATA Spred Knots	0.0	11.4	17.9	16.3	14.8	29.4 18.6	15.1	18.1 32.0	2	26.9 28.2 21.5	247.4 24.6 27.7 37.7
	WIND DATA DIRECTION S DEGREES(TN) K	151.3		63.0					0 00 00 00 00 0 0 0 0 0 0			4 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0
	REL.HUM. Percent	42.	55.	47.	38°	27 . 19.	8 8 •					
2047220020 2047220020 TABLE-6	TEMPERATURE R DEWPOINT EES CENTIGRADE	7.0	. 40 4 E. 40	-10.9	-16.1	-28.3	-41.7					
; -	TEMF AIR Degrees	23.1	15.0	5.1	-4.1	-13.6	-24.3	-50.9	-64.0 -70.2	1-67-1	158.9	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
# S.F.	OPOTENTIA FEET	5118. 6842.	8651. 10555.	12564.	16966.	22078. 24979.	78203	40869	46834. 50437.	54812.	65073. 68903.	73641 79741 83694 94914
. 4010.40 FEET 0800 MDT 20	PRESSURE GEOPOTENTIAL MILLIBARS FEET	850°0 0°05°3	750 .0	650.0 500.0	0.000	4 4 5 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	0.000	2002	150.0 125.n	100 80 00 00 00 00	2000	204 205 205 206 206 206 206 206 206 206 206 206 206

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

TES	DEG
RDINA	207
27	0591
ETIC C(32.899)	9
96500	Ŧ

SIGNIFICANT LEVEL DATA

STATION ALTITUDE 3912.75 FEET MSL

23 JULY 82

ASCENSION NO. 83

PRESSURE GEOMETRIC TEMPERATURE REL.HUM.

AIR DEWPOINT PERCENT

PRESSURE GEOMETRIC TEMPERATURE
ALTITUDE AIR DEMPOINT
MILLIBARS MSL FEET DEGREES CENTIGRADE
53.7 67696.6 -53.0
50.0 69218.6 -52.7
44.5 71700.7 -53.5

S FEET MSL MDT TEMPERATU	MSL			REL-HUM	CER AID 28 28 LE-3 LE-3	A A A A A A A A A A A A A A A A A A A	•	6E00ETI 32. 106.	C COORDINATES 89927 LAT DEG 40591 LON DEG INDEX
w	AIR DEWPOINT PE EGREES CENTIGRADE	OINT PE	w	2		SOUND	DIRECTION DEGREES(TN)	SPEED	OF REFRACTION
•6 25.0 16.	5.0 10.	٠	4	•	50	9.4.9	70.0	1.9	1.000285
2.07 8.45 71.2	11.2	7.5	•	~	626.	7.	;	•	• 00058
7.7 25.2 12.	5.2 12.7	2.7	4	*	90	~	91.	•	.00028
2.8 24.6 12.0	4.6 12.0	0.0	•	Š	91	7	ċ.	•	.00028
8.1 23.4 11.5	3.4 11.5	1.5	4	.	78.	M	90	•	•00027
3.6 22.2 11.2 4	2.2 11.2 4	1.2 4	4 1	O 1	7.596	671.6	88.7	ا رم ه	
C 8-01 D-17 5-6	S 8-0L D-L	2 · 0	n i	•	25	э.	;	•	97000
5 1909 3001 505	5 1.01 6.6	נים נים	'n	•	9	201	;,	•	97000
2 4.6 8.8 5.1	0 4°6 20°1	41	7	•	92	┗,	٠,	٠,	:2000
2 1.0 1.1 Co.	S 1.00 1.1	^ ·	~ ;	•	•	ο.	;	ġ,	<2000.
2.5 Jose 8.5 J	7.8	, .	~ ;	•	20	•	۸.	٠,	<2000°
0 /0/ 6091 600	0 101 605	•	0	•	0.0	∽.	•	;,	*700
0 100 400 100	0 [0]	·	0 3	•	• :	- (•	•	*7000*
0 (00 000	0	۰.	6	•	, c	> (٠.	:.	. 7000
		•	0	•	• • •	70	ė.	٠,	2000
		20	òv	•		۰ ۵	• •	•	
7 4 1 - Cas 6 - Cas 7	7	104	, K	; -		٠.	9		02000
1.8 7.0 -3.7	-3.7	3.7	4		60	m		•	.00020
9.9 6.0 -5.6	•0 -5•6	5.6	•	'n	96.	-		•	.00019
8-1 4-7 -6-8	-6.8	80.0	•	'n.	85.	0	۲,	Ġ	00019
2001	7.0	.	•	• .	į:	1 0 1	ŗ,	٠. ١	-0001
0-04- 2-4 -40-0	6,01	^ O	• -	5 0	9.5	644	•	•	
A 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	-12.3	200) P		07	•	, ,	, ,	71000
1.56 -13.7	-13.7	3.7	M	•	29.	m		, p	.00017
0.8 -1.7 -15.0	1.7 -15.0	2.0	M	\$	8.	~	-	•	00017
0.2 -2.8 -16.5	2.3 -16.5	6.5	m	ň	08	9		-	•0001¢
9.7 -4.0 -18.0 3	4.0 -18.0 3	8.0 3	M	٠	97.	0	÷	•	•00016
9.3 -5.2 -19.5 3	5.2 -19.5 3	9.5 3	×	•	8.7	00 F i		•	.00016
5.2 -6.4 -71.0 3	6.4 -21.0 3	1.0	M	•	77.	9 ½	•		.00015
9.2 -7.6 -22.6 2	7.6 -22.6 2	2.6 2	28		67.	35	۲.		.00015
5 7-4- 28-6 -24-7 2	8.6 -74.7 2	4.7	25	•	57.	1	٠,		.0001
2 -2 -2 -2 -2 -2 -2 -2 -2 -2 -2 -2 -2 -2	8.8 -75.9 2	5.9	2		. 2	2	•		21000.
Ca2 -9.4 -27.1 2	2 -27-1 2	7.1 2	•	•	34	42	٠,٠	•	-00014
# ac 4 0 # 4 0	9 0 0			, ,			٠,	•	71000
1 07 0 0 1 0 1 0 1 0 1 1 0 1 1 0 1 1 0 1	2001	- (•	•	•	- (٠.	•	
	0.621) (N 1	•	•	0.00		\	41000
	ラ・ロット フ・ウ・マー) (• •	•	•	10	•,	• c	1 6 0 0
	10101 C101	، • د		4 :		- 6	٠,	•	
2011 COC - 915	2007) •	`	•	0	Ç	•	•	• 0000

STATION AL	LETITUDE 391	912.75 FEET MS 0900 :10T	ET MSL	_	100 EH AIR 204029001	83 83		GEODETI 32.	∵ ∞
SCENS IO	60	•			BLE-8	cont'd			40591 LON DE
w _	PRESSURE	TEMF	PERATURE DFWPOINT	REL.HUM. Percent	DENSITY GM/CUBIC	SPEED OF Sound	WIND DIRECTION	ATA SPEED	INDEX Of
144	MILLIBARS	œ	ILN		ETER	KNOTS	S (NO T	REFRACTION
5500.	425.6	•	33.	17	78.		a ∪		1.000111
4000	~			2	69	~	C	•	.00012
4500		C	S	2.	c	_	b	6	00012
5000		ပ်	•	3	52.	0	6	m	.00012
5500.	~	21.	•	3.	43.	8	0.5	5	.00012
•000	•	?	7,	~	P 3	~	∞	•	00012
6500	•	12.		÷	22.	~	C .	æ	.00011
7000	0	2	30	-	12.	v	0	28.5	.00011
7500	•	23		.	03	9	ò	6	.00011
0000°	•	4	0.4	÷	. 76	~	70	ċ	.00011
8500.	•	4	9	.	60 I	-	90	ċ	000010
9000	0	13	4.1	.		м.	20	÷	•00010
\$500 •	N 1	9 1	9	.	60		90	•	01000
0000	~	72	3:	.	29	7	500	Ď.	-0001
0000	20 (90	3;	;,	, ,	> (3 6		2000
9000		, (S		÷,	*	.	2	'n.	70000
1500.	n 6	() 	4 .	. .	90	no.	80	2	60000
	A		ζ;	: ,	•	0 6	5	•	00000°
	. .		A . C	<u>.</u>		^ *	. u	•	
4500	9 6	ر بر کر	4	• •	- C	ን ሌ	٠. د	• •	
2007		2 1	40	. ,-			U 1	•	0000
450C	- 00	9	S	21.1	96	0			-0000
5000	~	~	2	-	-1	8	7	۲.	.0000P
5500.	ø	13	C .3	÷	87.	~	4		.0000°
6000	_	0	25	. 3	14.	.	L	•	*0000°
36500.0	245.6	9.07-	->4-7	15	0.895	400	F. 6	9.71	1 000082 1 000082
- C C C C C C C C C C C C C C C C C C C	> <	- ·	0 0		• L		. •	•	00000
		•	, ,		•	- 0	, •	•	
	> 4	7-57-	• 7 4		 	~ ~	u P	• (
	1 0	, 4	. V		7 7	. •	٠.	•	7000
		7.7				•	r.	•	7000
	7 0	- 0		. 4			. •		7000
	204.8	. C	•	•) () () (. ex	1000
		,			1.	. 0		Ċ	7000
	200	· U			, a	٠. م			
	١ د	. .			• • (٠. ١	• ,	
	> •	 			٠,	0 4	0 0	;,	00000
, y u c .	•	<u> </u>			ر بر	O u	٠,		
0000	0.346	6.7				\sim	,	7.0 7	9000

** AT LEAST ONE ASSUMED RELATIVE HUMINITY VALUE WAS USED I'S THE INTERPOLATION.

COORDINATES 19927 LAT DEG 10591 LON DEG	INDEX OF Refraction	1.000063	9000	0000	2000 2000 3000	0000	20000	900	20000	20000	9000	0000	90000	200	00000	00000	10000	, ,	0000	₽0000		000	9 6	0000	0000	₽000	000	0000 t	000	2007	20000	1.00003
GEODETIC 32.8 106.4	TA SPEED KNOTS	25.5	e -			c.	•	. ~	2	ĸ.		-	•	36.7	•	3.	2	- c		•	•	'n.	•		· •	:	ċ	ċ	۲.	· .	÷.	23.7
	WIND DATE DIRECTION S	80 80 5 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9	3.0		v. r		-,	• ;	9	. c	دع ج		Ġ	r. v	, ,	,	Š	•	•	Š	٠.	ě.	• '	• •		•		\$	•	ru.	r (• •
DATA 83 nt'd	SPEED OF Sound Knots	574.2	71.	689	67.	4	63,	60.	29	88.4		56.	54.	5.6	86.	56.	56.	. 9 y	2.5	57.	57.		0 0	60	62	63.	65°	67.	66.	99	. 59	0000
UPPER AIR DATI 2040290083 E-28 TABLE-8 conti	DENSITY GM/CUBIC METER	284.9	74.	5 %	50 K	6.4	7 7	34.	50	400		13	90	070	69	24.	•	× +		٠,		•	•	, ,		6	60	\$.,	•	٠,	
J .	REL.HUM. Percent																															
12.75 FEET MSL 900 MUT	TEMPERATURE AIR DEMPOINT DEGREES CENTIGRADE	9.5%- 0.5%-	56.	60	61.	63	* "	66.	67.	• 4 9 4 9 4 9 4 9 9 9 9 9 9 9 9 9 9 9 9	• •	70.	P (170°4	. 6	68.	S 8	-69.0	63.	68.	83	;;	• (66.	65	63.		61.		۲,	, v	-62.1
ITUBE 39 0 83	PRESSURE MILLIBARS	177.7	6.5	: -	. M	20.	9 0	39.	32	320	25.	22.	19.	÷ .	5	08.	92	200	97.	Š	٠,	٠,	• 4	•	-	ċ	æ	Ģ	,	?	ံင	7.
STATION ALT. 23 JULY 82 ASCENSION N	GEOMETRIC Altitude MSL FEET	43500.0	4500 .	5500	6000°	2000	7500.	\$50C.	\$000	9500	5500.	1000	1500.	2000	3000	3500.	4000	4500°	550C.	• 000 o	6500.		, 0000 c	8500	•0005	\$230.	0000	C 200•	1000	1539.	2007 2007	3000

STATION ALTITUBE 23 JULY 82 ASCENSION NO.	M1 M1	0900 1DT		UPPER AIR DATA 2340296083 F-28 TABLE-8 contid	eara 383 ont'd		6E00E71 37.	GEODETIC COORDINATES 37.89927 LAT DEG 106.46591 LON DEG
GEOMETRIC Altitude MSL Feet	PRESSURE MILLIBARS	TEMPERATURE AIR DEWPOINT DEGREES CENTIGRADE	REL.HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF SOUND KNOTS	WIND DATA DIRECTION S DEGREES(TN) K	SPEED KNOTS	INDEX OF REFRACTION
63530.0	65.7	-61.8		108.3	566.3	125.8	23.2	1.000074
64000.0	64.1	-61.6		105		125.9	22.1	1.00003
64500.0	62.6	-63.8		102.7		123.4	20.7	1.000023
65736.0	61.1	-59.6		40.0	269.3	117.0	21.2	1.000022
63500.0	29.7	-58.4		8.96		66	24.5	1.0000-2
0.00099	58.5	-57.1		94.		9,0	2002	1.000071
56500.0		-55.9		21.2	2. 376.2	8.8	34.5	1.000020
67000.0		-246.1		88		37.0	38.8	1.000020
87500.0		-53.5		86.0		88.6	36.7	1.000019
68005.0		-52.9		¥ 9		90.8	34.6	1.000019
66500.0		-52.8		81.8		89.6	31.3	1.000018
69000.0		-52.7		79.8		₽° 80	28.1	1.000016
69500.0		-52.8		78.		87.1	27.3	1.000017
2000°		-53.0		76.3		36.0	27.8	1.000017
70500.0		-53.1		74.5				1.000017
71000.0		-53.3		72.	577.7			1.000016
71500.0		-53.4		71.2				1.000016

.

í

130

A CONTRACTOR

SIGNIFICANT LEVEL DATA	120023023	UM 37	TABLE-10
	IION ALTITUDE 4716.40 FEET MSL	JULY 82 1100 MIT	INSION NO. 31 LE CON NOISH

GEODETIC CUORDINATES 32.28497 LAT DEG 136.49714 LON DEG

PRESSURE	EOMETR	-	FIURE	REL.HUM.
MILLIBARS	MSL FEFT	DEGREFS	CENTIGRADE	F K C E
F)	5	•	÷	8
76.	273.	É	-	,
۲. د	173.	•	•	
79.	674.	<u>"</u>	å	,,
£7.	317.	5	•	m
0.00	3598.	-	•	8
651.8	\$5544.4	7.0		47.0
9.07	3012.	ن	•	•
2.69	6156.	:	•	
57.6	.2.89	2	15.	8
0.00	9511.	7	~	~
3.9g	0194	w	26.	÷
8.93	• 7697	:0	. 7.	
6. 40	4 3054	16.	* *	()
0.00	5138.	17.	44.	Ġ
7.76	5456.	17.	'n	ċ
77.2	7305	ن	9	2
0.00	2028.	10		
2.0	4300	,	6.4	()

406.8 24692.8 1794.4 170.0 25108.2 1794.4 2500.0 25108.2 179.2 270.0 370

GEODETIC COORDINATES 37.98497 LAT DEG 106.49714 LON DEG		
SIGNIFICANT LEVEL DATA 2040220021 Nu 3C TABLE-10 contid	TEMPERATURE REL.NUM. AIR DEMPOINT PERCENT DEGREFS CENTIGRADE	-46.4 -45.4 -47.5 -45.4 -43.1
IN ALTITUDE 4710.40 FEET MSL Y 82 1100 MDT IION NO. 21	PRESSURE GLOMETRIC ALTITUDE MILLIBARS MSL FEET	30.0 80333.9 29.2 80929.1 23.2 85982.6 20.0 89244.8 14.3 96693.6

TATION A	LTITUDE 491	010.40 FEE'	ET MSL	-	UPFER AIR	DATA 21		GEODET	COORDINATE
JULY P		1100 HDT			S BN			ä	86497 LAT DEG
Sc	NO. 21			•	TABLE-11			~	9714 LON DE
EOMETR	PRESSURE	TEMP	ERATURE		ENSITY	SPLED OF	AG GNI A	-	INDEX
ALTITUDE			DEWPOIN	ENT	/CUBIC	SOUND	IRECTION	SPEED	0
SL FEE	MILLIBARS	œ	NIIGRA			KNOTS	REES	NOT	REFRACTION
710.	٠ س	-	-	٠ ټ	60	82.	6	•	5027
500	ø		-	Š	0	, ~ ·			000E7
200.	53.	•	:	ů	86.		2.5	•	.00027
500.	*	5	ပံ	÷	74.	74.	1.4	•	.00027
000	24.	ň	•	'n	62.	73.	36.	•	•00026
00:	ċ	12.1	ċ	2.75	50.	4.1.2	127.7	3.1	326
- 00-	9	ċ	•	æ	36 9	69.	<u>, </u>	•	•30026
50G	82.	¢.	•	-	26.	68.	12.	•	\$2000°
9	80 9	~	•	;	7	•	0	•	• 0005
200	54.	÷	•	÷	3.	•	<u>, </u>	•	*2000°
000	41	Š	•	٠	51.	'n	7,	•	*2000
. CDS 5	82	6	٠	:	79.	•		•	00054
.000;	73.	* (*)	6.7	ů	67.	ċ		•	023
6300.	25	2	٠	7	55.		13	·	•00052
1600.	80	Ü	٠	S	W.		ċ	ė	12000-
1500	7.	•	.	Š	• • •	÷	9.	÷.	.00021
- 202 T	64.	۵. د .	٠,	•	()	•	٠.	-,	020
2500	52.	•	'n.		60	* *) (2	.	02000
	9	•	•		9	~	•	2	.00019
.500	62	2.4	ġ.	.		ا ق	7.	<u>.</u> ,	• 00019
	_;	•	•		ċ		٠,	•	2 6
	•	•	•	•	֓֞֝֟֝֓֓֓֓֟֝֝֟֝֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֟֝֓֓֓֓֓֡֓֡֓֡֓֡	•	• ;	•	
	• • •	-		•	• • •	•	• • •	• ,	L &
000	, ^ , ^	•	9 (9		, M	•	• •	; ;	71000
6530.	6.1	2		8	114		, ·	,	17
7000	51.	-3.1	13		10	ن	5	۲,	00016
750C.	40	,	17.	š	99	Š	6	~	318
,000°	Ġ	ń	ŝ	.;	88.		50	-,	116
850G.	0.	ŝ	23.	÷	77.	2	Ċ	;	1000
90009	_	3	7:	œ.	99	Š	ď.	\$	Ë
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	ည ပ	٠	2		5.	•	•	š	313
2002	G.	m	5		44.	•		÷	00014
.20C	80.	•	27.	-	3.6	*		•	114
1200	7	ċ	25.	.	. , ,		÷	ç	0001
1500.	29	-11.2		.	7.	ċ	α . Ο .	•	210
20.3	M .	L1 1	5.2	.	. 70	•		•	.0001
	. 5 7	-	•	-	ان	Š		•	. 1001
0.00000	4.7.4	7.7.	-31.5	21.6	76597	576.8	6 () () () () () () () () () (ن 1000	1.000173
0000	9		•	-	٧٤.	•		•	1000

STATION AL 23 JULY 82 ASCENSION	TITUDE 40 1 NO. 21	10.40 FEET 100 MDT	ET MS.L		UPPER ATR D ZO4022002 NW 30 TABLE-11 CC	DATA 021 cont'd		GEODETIC 32.8 106.4	IC COORDINATES -88497 LAT DEG -49714 LON DEG	
EOMETR	PRESSURE	168	PERATURE	REL.HUM.	DENSITY	SPEED OF	A IND DA	TA	INDEX	
ALTITUDE MSL FEET	HILLIBARS	AIR Degrees	DEWPOINT Centigrade	₩ ₩	M/CUB Meter	SOUND KNOTS	DIRECTION Degrees(TN)	SPEED	OF REFRACTION	
4000	18.	-16.5	m	-	67	24.	113.6		1.000129	
450C.	60	-17.6	-34.1	~	58	~	-	23.0	00012	
5000	01.	17	4.	ပ	9	23.			00012	
5500.	93.	-17.5	Š	O	36	23.	2		00012	
•0009	85.	-18.4	-35.7	C	1,1	21.	4	•	00011	
9 200.	78.	-19.4	•	•	518.8	20	137.7	23.2	00011	
7000	20.	25	-36.5	~	C	19	-	•	00011	
7500.	29	5.5		•	5	2	œ.	•	.00011	
8000	,,	25	4	_,	5	9;	٠	•	.00011	
		2000	# * C * 1	- •	ŝ	_;	÷,	•	01000	
		25.4.5			7.7.4		•	•		
0000	,	, 6	1.74	- C	2 5	<u> </u>	• (• (
C 500	0	75			. M	- 0	, N	22.7	00000	
10001	13.	-28.7	•	0	9	6	•		010	
1500.	90	-29.7	-45.3	O	3	6	v	•	•0000	
2000	90	-30.7	-46.2	0	31	8	r		600	
.506.	96	-31.6	-47.0	0	53	5	. .	•	60000 •	
2000		52.5	7:	0	26	3	m,	•	40000°	
7000		123.3	9 0	3 C	9 -	၁င်	~ 4	•	40000	
4530	9	13.50	-51.1) r	50	9 C) K	• •		
0.0005 ¥	263.8	6.92-	N 9 8 1	12.7**	0.00	0 00 0 00 0 1/1	600	29.5		
5500.	58.	-78.5	ပ	-	80	8	∞		.0000	
6 000.	52.	0.03-	C	•3	17	76	•		0000	
6500.	46	-41.3			20	5	L 1	•	0000	
7000	-	-42.2			64	26	•	•	.0000	
	9	-45.2			5	0 6	,	•	0008	
8000	30.0	0.44-			2	6	D (•	000	
8200	200				•	D-0	P / 1	•	0007	
	•	3:			200	10 F		•	20000	
0000	•	9!			3:	200	٠ ،	•	000	
	9				9 ;	80	•	28.6	0000	
2000	•	•			R. (•	•	1.00001	
0001	• []	, ,			2	10 10 10	•	•	000	
200	90	2001			9	22		27.4	0000	
0007	91.	-51.1			5	C) ((n (28.1	9000	
1000	2 2	4 1/			297.65) I	ايدا	5 ° 6 ° 1	9000	
ם מפרי	• •	4.000				<u>,</u>	•	2005	90000	
• 0000	0) • • •	2	•	0 - 0	9000	

** AT LEAST ONE ASSUMED RELATIVE HUMINITY VALUE WAS USED IN THE INTERPOLATION.

IC COORDINATES: B6497 LAT DEG: 649714 LON DEG	INDEX OF REFRACTION	0000	1 000000000000000000000000000000000000	0000	20000						2	0000	00000000000000000000000000000000000000
6E0DET1 32•	TA SPEED KNOTS	• •	4 4 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6	W W W W	• •	• • •		24.9		M W W W W W W W W W W W W W W W W W W W	1045. 1969 1988		14 E V V
	WIND DATE DIRECTION SEGREES(TN)	6 9 9 9 9	# # # # # # # # # # # # # # # # # # #	112.7	/ b ~ C C	420.0	118.6 116.6 113.3	0000 0000 0000 0000	14 NO	0 W P P P		910	
para g21 cont'd	SPEED OF Sound Knots	574.4	569 569 569 569 569 569 569	10 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	X X X X X X X X X X X X X X X X X X X	557.9	555 554.9 554.9	55 55 55 55 55 55 55 55 55 55 55 55 55	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	2 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0		55.00 570 570 570 570 570 570 570 570 570
UPPER AIR DATA 2040220021 NW 30 TABLE-11 cont	DENSITY S GM/CUBIC METER	279.6	9 4 6 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	200 200 200 200 200 200 200 200 200 200	2000 2000 2000 2000 2000 2000 2000 200	27.9	11. 07. 02.	197.7	1000		00 00 00 00 00 00 00 00 00 00 00 00 00 00		
-	REL.HUM. Percent												
ET MSL	PERATURE Dewpoint Centigrade												
4010.40 FFET 1100 MDT	TEMPE AIR DEGREES C	20.00	1 50 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	625	1 0 0 0	1.88	-69.5 -70.3 -71.1	14000	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	0000	
TITUDE No. 2	PRESSURE MILLIBARS	72	0 	·	4 4 6 6	PJ M	23. 20. 17.	4-84) D D D 0	0 22 24 34 4		20 40 41 F	6667
STATION AL 23 JULY B2 ASCENSION	GEOMETRIC Altitude Msl feet	4500.	2000	7000	6 5 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	0000	1000. 1500. 2000.	1000°		7000	6500 5000 9500	1000	6 15 00 00 00 00 00 00 00 00 00 00 00 00 00

STATION ALZ 23 JULY BS ASCENSION	LTITUBE 40] 2 80. 21	10.40 FEET	J.S.E.		UPPER AIR 20402200 NW 30 TABLE-11 C	0021 cont'd		GEODETIC 32.8 106.4	IC COORDINATES •88497 LAT DEG •49714 LON DEG	
	•		124		,					
₩!	PRESSURE	-	EMPERATURE	֭֝֟֜֜֜֝֝֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֡֜֜֜֜֜֓֓֓֡֜֜֝֓֜֜֜֜֜֜֜֜֜	ENSITY	EED	ONIA	1	INDEX	
MSL FEET	FILLIBARS	DEGREES CE	NTIGRADE	FENCEN	METER	KNOTS	DIRECTION DEGREES(TN)	KNOTS	OF REFRACTION	
0004	•	59.	-		•	569.	6	11.6	2000	
4500	3	5			-	569		17.9	20000	
5000	÷	-58.8			•	570.		26.8	20000	
5500	å	£8.				571.	ň	36.1	20000	
0009		~			2	571	÷	37.4	20000	
6200					2	572.	ċ	34.7	20000	
7000	j,	20			0	573	F	•	20000	
7530	÷.	-55.9				574	2.96		0000	
	å,	??			, N	275			0000	
200	:.	* *				•				
	• •	~ "			- 6	ė;		•		
	•	•			> 1	77.	٠.	e e		
0000	: .	S			75.5	٠,		'n	000	
1000		53	•		٠,			30.7	1,000016	
1500		1	•			76.	2	•	0000	
0007		3			•	76.	•	•	0000	
2500	'n	;			6 0	576.8		š	0000	
3000	ň	54.0			67.2	~	ď.	;	0000	
3500	÷	-54.1			Š	576	60		10000	
000	å.	;			;	76.	ė.	۲.	5	
6500		S)			2	76.	-	•	0000	
2000		24.				40.	 () (Š.	0000	
5500	٠.	Š			•	•	•	4 1	0000	
	: .	*				•	Ď,	÷,	5 :	
7000		0 10 10 10 10 10 10 10 10 10 10 10 10 10			0.00	70/10	* • • • • • • • • • • • • • • • • • • •	9 4 6	2 10000° 1	
	;					9 0	•	•		
0000		17			•	- 44	•		000	
8500	2	6				- C		. ;	10000	
0005	: -	6.8			•	1	v c	• •	-	
0055	-	8				98		9	00001	
0000	ċ	~			•	385	7		0000	
.505	6	-46.1			45.07	87.	P. * 6	•	10000	
1000	•	-45.4			44.5	۲.	ບ•ຸ 6	ċ	5	
1500	8				4.5	587.6	*°C*	•	5	
8,000.0	2.7.8				42.5	587.4	8 . 7	•	2	
0000		69			•		.	•	000	
0000	ġ.	9			Ø, € 0.4	•	& (55.5	000	
3500	ċ	- 46.5			•	5.98.	•	•		

STATION AL 23 JULY 82 ASCENSION	ALTITUDE 4910,49 FEET 82 1100 (101 1N NO. 21	10.43 FEE	7 #SL	~ F	UPPFK AIR DATA 2740220021 NM FR TABLE-11 cont'd	DATA 21 ont'd		6E0bETIC 37.8 106.4	ETIC COORDINATES 32.88497 LAT DEG 06.49714 LON DEG
GEOMETRIC Altitude	PRESSURE	TEMP	TEMPERATURE Dempoint	REL.HUM. PERCENT	DENSITY GM/CUBIC	SPEED OF Sound	WIND DA	DATA	INDEX
MSL FEET	MILLIBARS	DEGREES	CENTIGRADE			KNOTS	DEGREES (TN)	KNOTS	REFRACTION
0007	25.4	7-66-7			39.1	586.3	76.7	24.5	1,00009
4530	,	-46.9			38.2	•	77.8	25.4	1.000009
\$5000.0	24.3	-47.1			37.4	585.7	7.27	27.6	1.000008
5505	'n	-47.3			36.6	س	7.0	29.8	1,000008
0000	ň	-47.5			35.8	•	72.6	32.1	1.000008
2059	5	-47.2			34.9	585	7	31.4	1,000008
7000	2	-46.3			34.1		72.2	30.7	1.000008
7500	÷	-46.5			33.3		72.0	30.1	1.000007
8000	21.2	-46.2			32.5		74.3	31.3	1.000007
850 0	ċ	6.57-			31.7		78.	34.3	1.00007
3006	å	-45.6			31.0		81.7	37.5	1.00007
0055	ċ	-45.3			30.2		9.78	4004	1.000007
2000	•	-45.2			29.5		86.0	36.6	1.000007
0050	8	-45.0			6.82		8,48	36.8	1.000006
1000	8	6.44-			28.2		87.8	35.1	•
1500	8	-44.7			27.6		91.8	32.1	
2027		-44.5			56.9		6.36	28.1	1.000006
2500		-44.4			26.3		•	24.3	1.000006
0001		2.44-			25.7		102.0	20.5	1.000006
2500		-44.1			'n	589			1.000006
400C	÷	-43.9			4	589.			1.000005
4500		-43.8			24.0	390			1.000005
2000	•	-43.6			23.4	Ŋ			1.000005
5500	•	-43.5			6.23	יי			1.000005
8000	•	-43.3			7.22				1.000005
6500	14.4	-43.2			21.8	290			1.000005

STATION ALTITUDE 23 July 82 Ascension No. 7	DE 4010,40 FEET #SL 1100 MUT	18# 1		MANDATORY LEVEL 2040220021 NW 30 TABLE-12	EVELS 21		GEODETIC COORDINATES 32.88497 LAT DEG 106.49714 LON DEG
	PRESSURE GI	PRESSURE GEOPOTENTIAL	, 4	TEMPERATURE	MEL.HUM.	Ad duly	TA
	MILLIBARS	FEET	DEGREES	CENTIGRADE		DEGREES (TN) KNOTS
	850.0	5120.	26.2	11.2	39.	156.3	2.2
	0.00%	6859.	21.1	4.6	8.4	121.5	. de
,	759.0	8678	16.0	7.6	57.	111.6	0.4
	100.00	10588.	11.8	₩.	45.	122.2	10.0
	0.059	12606.	6.7	-3.9	.97	114.5	11.9
	630.0	14749.	2.1	-7.5	.64	114.4	11.1
	220.0	17031.	-3.2	-15.7	37.	112.3	
	0.00	19484.	-7.9	-23.6	27.	P. 86	15.7
	0.027	22151.	-12.6	-30.1	21.	102.6	18.1
	0.004	75067	-17.0	-34.5	20.	128.7	24.8
	350.0	28317.	-23.5	-39.1	21.	122.2	22.5
	ŭ*00.	11965.	-30.8	-46.3	20.	107.2	23.5
	250.0	36137.	1.03-			105.2	24.5
	0.007	41032.	-49.1			£9.0	27.4
	175.0	43865.	-55.6	:		9.10	33.5
	150.0	47032.	-63.2			110.6	36.0
	125.0	50652.	-69.5	:		-	31.5
	100.0	55017.	-68.7	•		102.3	28.1
	80.08	29449.	-62.1	:		112.4	•
	20.0	62183.	-59.0			137.7	0
	. 0°09	65356.	-58.1			102.9	37.2
	20.0	69163.	-53.6			98.7	7.85
	0.04	73865.	-54.2	-		91.0	33.1
	30.0	79989.	1.91-			93.8	32.6
	25.0	83967.	8.94-			74.0	24.5
	20.05	88824.	-45.4			85.9	38.8
	15.0	95147.	-43.4				

** AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

GEODETIC COORDINATES 32.89927 LAT DEG 106.40591 LON DEG

REL.HUM. PERCENT	WW44999WW44WW4WWWWWWWWWWWWWWWWWWWWWWWW	
EKATURE Ufwpoint Centigrade		
TEMPE Air Degrees		•
GEOMETRIC ALTITUDE MSL FEET	12 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	, ,
PRESSURF MILLIBARS	######################################	•

GEODETIC COORDINATES 37.89927 LAT DEG 106.40591 LON DEG

STATION ALTITUDE 3912.75 FEET MSL 23 JULY 82 1215 MDT ASCENSION NO. 84

REL.HUM. Percent

TEMPERATURE AIR DEWPOINT DEGREES CENTIGRADE

PRESSURE GEOMETRIC ALTITUDE MILLIBARS MSL FEET

538759 538695 538695 637690 63756 66756 68799 71720 71720 71720 71720 71720 71720 71720 71720 71720 71720 71720 71720 71720

STATION AL 23 JULY 8; ASCENSION	LTITUDE 39. 2 86 1	12.75 FEE1 1215 ADT	T	· .	JPPER AIR 20402930 E-28 ABLE-14	8 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4		GEODETI 32. 106.	C COORDINATE 89927 LAT DE 40591 LON DE
GEOMETRIC Altitude MSL FEET	PRESSURE	TEMP AIR Degrees	PERATURE Dewpoint Centigrade	REL.HUM. PERCENT	DENSITY GM/CUBIC METER	SPEED OF Sound Knots	WIND DA DIRECTION DEGREES(TN)	TA SPEED KNOTS	INDEX OF REFRACTION
912.	85	÷	14.0	34.0	1004.1	82.	0	O.	8 U
000	82.	-			1003.4	-	'n		~
500.	67.		•	ċ		79.		•	ec.
000	52.	ŗ	•	:	_	77.	Ņ		8
200	38.	š	•	ċ		75.	Ġ.	•	2
900	23	•	11.2	•	9.88.6	•	٠. د	6.0	900
500.	60	'n.	•	;		72.	.	•	~
200	56	÷,		ń,	434.0	7.	÷,	•	2000
900	91	5		ċ.	_	60	ġ.	•	2000
		• •	•	•	•	• • • •	•	• • •	
		•		• .	_	ė	0 M	•	4 0
2005	27.	•	• •		876.0	. K	, -	• •	0002
0000	15.		•				ς,	. 6	000
C530.	02.	2			851.1	60.	Ç	Š	000
10001	89.	•		÷		58.	÷		000
1500.	77.	6	•	ň		57.	<u>;</u>	•	~
.000		•		;	_	24	••	•	1.00021
0000	•	•	-1-7		_ ` .			• •	00000
3500	29.	• •	٠ ٨	;		7	ċ	: .:	0001
4000	17.			Ġ		50.		Š	6000
4500.	90	3.6		š		48	۴.	5	000
5000	94.	•	æ	÷	_	47.	۳.	•	000
200	'n.	~ •		4 F	744.1	n	•	12.6	
6500.	6.2	0 0 0 -	0.01-	• 4	_ ` .	7	· -	- 6	7
7000	51.	m	=			9	• ,•		000
7500.	40.	-3.6		္ပံ	_	60	ů		00016
*0007	30.	4.4-	÷			39.	,	5	00016
6500.	20.	-5.4		~	_	37.	4	•	0001
9000	0	•	ċ	-		36.	÷	•	٠
9500.	9	•	24.	ij	_	9	ċ	·.	0001
ננממ•	90		22	-	-	9	~		*
	81		92	Ė,		'n,		0C (_
	::	.	• (_	200	٠,	•	\$1000
2000	• 70	2 :	10	. .	4.4.6	• • •) C	•	41000
	• · ·	- ;	• > •	. د		, ,	٠,		200
0.00000	4 4 4 4 6 0	13.0				7.020	0 + 1	4.4.	6. LOOD . L
	•	•	•	ı	_	-	•		

E S

41		32.89927 LAT DEG	
UPPER AIR DATA	204020184	E-28	TABLE 14 COUNTY
	UDE 3917.75 FEET MSL	1215 MDT	40
	ATION ALTITUDE	28 Alnf S	CENSION NO.

THELE—14 CONT. 14 THELE—14 CONT. 14 L FET PREATURE REL.HUM, DENSITY SPEED L FET HILLIBARS DEGREES CENTIGRADE ROOF AND AND AND AND AND AND AND AND AND AND	THE PRESSURE TEMPERATURE RELHUND DENSITY SPEED OF LAIDS DATA TO SECURE THIS PRODUCT SOUND DESIGN TO SECURE THIS PRODUCT SOUND DESIGN THE PRODUCT SOUND DESIGN THE PRODUCT SOUND DESIGN THE PRODUCT SOUND DESIGN THE PRODUCT SOUND DESIGN THE PRODUCT SOUND DESIGN THE PRODUCT SOUND THE PR	ION A ULY 8	LTITUDE 391 Z	215 MDT	ET #SL		UPPER AIR 2000 2000 E-28	0 A T A 8 4.		ET1 32.	ပေလေ
FIRE PRESSURE TEMPERATURE RELAMUM DENSITY SPREED FOR SOURCE SOURC	THE PRESSURE TEMPERATURE REL-HUM DENSITY SPEED OF WIND DATA REPORT OF THE PRESSURE TEMPERATURE REL-HUM DENSITY SPEED OF WIND DIRECTION SPEED OF THE PRESSURE TEMPERATURE REL-HUM DENSITY SCHOOL DIRECTION SPEED OF THE PROPOSAL SCHOOL SPEED OF THE PROP	C E NS I ON	NO. 84			L	ABLE-14	ont'd		•	46591 LON DE
March Marc	Compared by Comp	ETRI TUDE	PRESSUR!	TEM AIR EGREES	PERATURE DEWPOINT CENTIGRAD	EL.HUM ERCENT	DENSITY GM/CUBIC Meter	PEED Sound Knots	WIND DA Direction Egres(TN)	TA SPEE KNOT	INDEX OF
Mark	COORDINED 1.78)	
### ### ### ### ### ### ### ### ### ##	10001	3500.	27.	7	35	ပံ	76.	929	÷	š	.0001₹
\$5000.0 \$410.4 = 17.1 = 34.2 \$26.9 \$54.7 \$624. \$500.0 \$386.2 = 16.0 = 35.7 \$200.0 \$54.7 \$624. \$624. \$500.0 \$386.2 = 17.0 = 35.9 \$21.0 \$524.7 \$624. \$624. \$386.2 = 17.0 = 35.9 \$21.0 \$524.7 \$624. \$620.0 \$360.0 \$360.2 = 17.0 = 35.9 \$21.0 \$620.0 \$360.0 \$360.0 = 36.0 = 35.9 \$21.0 \$620.0 \$200.0 \$360.0 = 23.0 = 35.0 \$21.0 \$200.0 \$360.0 = 23.0 = 23.0 \$21.0 \$200.0 \$360.0 = 23.0 = 23.0 \$21.0 \$200.0 \$360.0 = 23.0 = 23.0 = 23.0 \$21.0 \$200.0 \$200.0 \$360.0 = 23.0 = 23.0 = 23.0 \$200.0 \$200.0 \$360.0 = 23	\$500.0 \$400.4 \$17.1 \$14.2 \$26.9 \$58.7 \$17.0 \$22.1 \$10001 \$500.0 \$400.4 \$17.1 \$14.2 \$26.9 \$58.7 \$17.0 \$22.1 \$10001 \$500.0 \$400.4 \$17.1 \$14.2 \$26.8 \$17.2 \$22.1 \$10001 \$500.0 \$400.4 \$17.1 \$17.2 \$17.8 \$17.0 \$17.	400G•	<u>.</u>	9	m		67.	929	Ġ		,00012
\$5000.0	1000	4500.	10.	17	3	ċ	5g.	623	ö	ċ	.00012
\$500.0 \$86.2 - 17.6 - 18.9 \$0000.0 \$86.2 - 17.6 - 18.9 \$0000.0 \$86.2 - 17.6 - 18.9 \$0000.0 \$86.2 - 17.6 - 18.9 \$0000.0 \$86.3 - 18.6 - 18.9 \$0000.0 \$86.3 - 18.6 - 18.9 \$0000.0 \$86.4 - 18.6 \$0000.0 \$86.4 - 18.6 \$0000.0 \$86.4 - 18.6 \$0000.0 \$86.4 - 18.6 \$0000.0 \$86.4 - 18.6 \$0000.0 \$86.4 - 18.6 \$0000.0 \$86.4 - 18.6 \$0000.0 \$86.6 - 18.6 \$0000.0 \$86.6 - 18.6 \$0000.0 \$86.6 - 18.6 \$0000.0 \$86.6 - 18.6 \$0000.0 \$86.6 - 18.6 \$0000.0 \$18.6 - 18.6	1000	2000	05.	7	רו	ċ	44.	624.	٠.	2	.00012
650000 378.4 -19.6 -35.9 21.5 500.0 378.4 -19.6 -35.9 21.5 500.0 378.4 -19.6 -35.9 21.6 500.0 378.4 -19.6 -35.9 21.6 500.0 378.8 -20.6 -35.9 21.6 500.0 378.8 -20.6 -35.9 21.6 500.0 378.6 -23.1 -23.1 -23.9 1 21.0 500.0 378.6 -22.0 -41.0 21.0 500.0 378.6 -22.0 -41.0 21.0 500.0 378.6 -22.0 -41.0 21.0 500.0 378.6 -22.0 -41.0 21.0 500.0 378.6 -22.0 -41.0 21.0 500.0 378.6 -22.0 -41.0 500.0 378.6 -22.0 -41.0 500.0 378.6 -22.0 -41.0 500.0 378.6 -22.0 -42.4 51.0 500.0 378.6 -22.0 -42.4 51.0 500.0 378.6 -22.0 -42.4 52.0 500.0 378.6 -22.0 -42.4 52.0 500.0 500.0 52.0 -22.0 -42.4 52.0 500.0 52.0 -22.0 -42.4 52.0 500.0 52.0 -22.0 -42.4 52.0 500.0 52.0 -22.0 -42.4 52.0 500.0 52.0 -22.0 -42.0 500.0 52.0 -42.0 -22.0 -42.0 500.0 52.0 -42.0 -42.0 500.0 52.0 -42.0 -42.0 500.0 52.0 -42.0 -42.0 500.0 52.0 -42.0 500.	1000	5500.	94.	16	•	ပံ	35.	623.	÷	2	.00012
\$500.0 \$70.0 \$	17.00	•0000	86.	17	4	Ġ	26.	622.	,	÷	.00011
7000.0 370.8 -19.6 -35.9 21.8 21.0 35.3 620.0 35.3 35.8 -21.8 -37.9 21.8 21.0 501.0	1000	650C.	78,	(0)	\sim		7,	621.	Ů.	5	.00011
7500.0 35.8 -20.6 -35.8 -21.9 501.0 519.8 500.0 35.8 -22.1	1000	7000	70.	19	~	÷	50	620.	4	•	.0001
600000	Mark	7500.	63.	20	v	;	2	619.	8	ċ	.00011
6500.00 348.6 341.4 -24.3 -41.0 352.6 352.6 352.6 352.6 -41.0 352.6 -41.0 352.6 -41.0 352.6 -42.0 352.6 -42.0 -42.0 352.6 -42.0 352.6 -42.0 -42.0 352.6 -42.0	3586 -23.1 -23.1 -23.1 -23.1 -23.1 -23.1 -23.2 -40.2 -23.1 -40.2 -40.7 616.2 116.9 24.8 10001 3564 -25.2 -41.7 21.0 461.4 612.5 116.9 27.6 10001 3574 -25.2 -41.7 21.0 461.4 612.5 116.9 27.6 10001 3574 -26.0 -45.4 21.0 461.4 612.5 116.9 27.6 10001 3574 -27.9 -45.4 21.0 461.0 461.0 1006.0 37.7 10001 1000 357.3 -27.9 -46.5 21.0 424.9 600.5 110.0 37.7 10001 2500 357.2 -46.5 21.0 424.9 600.5 110.0 37.7 10001 37.7 37.5 10001 37.7 37.5 10001 37.7 37.5 37.5 10001 37.7 37.5 37.5 10001 37.5 10001 37.5 10001 37.5 10001 37.5 37	£003	55.	۲	~	:	9.3	617.	۲,	2	.00011
950000	1000	6 500.	48.	23	O	÷	85.	616.	ď	•	00010
9500.0 937.6	1000	2005	£ 1.	54	n	÷	77.	614.	c		00010
000000 327.4	1000	9500.	34.	2	~	.	69	613.	ŝ	•	0001ب
1800	1000 15.4 20.8 21.0 45.4 21.0	0000	27.	3	*	- :	61.	612.	7	ċ	00010
150000 313.9	150000 307.3 -27.9 -45.6 21.0 445.9 610.1 109.8 32.0 100000 307.3 -29.2 -45.6 21.0 45.9 610.1 109.6 34.1 100000 300.9 -20.5 -45.6 21.0 45.9 608.5 109.6 34.1 100000 300.9 -20.5 -45.6 21.0 45.9 608.5 109.6 34.2 100000 294.5 -31.7 -46.5 21.0 45.0 608.9 109.6 34.5 100000 200.0 288.2 -32.1 -46.5 21.0 45.0 608.9 112.2 34.5 100000 200.0 288.2 -32.1 -46.5 21.0 45.0 608.9 112.2 34.5 100000 200.0 288.4 -28.1 -46.5 21.0 45.0 608.9 112.2 34.5 100000 200.0 25.1 -20	(500.	<u>.03</u>	56	2	÷	23.	611.	.,	÷	.00010
150000 288.2 -10.5 -44.5 21.0 438.9 608.2 20000 288.2 -10.5 -44.5 21.0 288.2 -44.5 21.0 288.2 -44.5 21.0 288.2 -44.5 21.0 288.2 -44.5 21.0 288.2 -44.5 21.0 288.2 -44.5 21.0 288.2 -44.5 21.0 288.2 -48.5 21.0 288.2 -48.5 21.0 288.2 -48.5 21.0 288.2 -48.5 21.0 288.2 -48.5 21.0 288.2 -48.5 21.0 288.2 -48.5 21.0 288.2 -48.5 21.0 288.2 -48.5 21.0 288.2 -48.5 21.0 288.2 -48.5 21.0 288.2 -48.5 21.0 288.2 -48.5 21.0 288.2 -48.5 21.0 288.2 -48.5 21.0 2	1000 100	10001	5.	22	m	-	45.	610.	ċ	2	.00010
200000 288.2 -31.4 -45.6 21.0 -42.0 608.3 2100000 288.2 -31.4 -45.6 21.0 288.2 -31.4 -45.6 21.0 288.2 -31.4 -45.6 21.0 288.2 -32.0 -45.6 2 -45.6 -45.6 -45.6 2 -45.6 -45	200000 2882	1500.	67.	20	4	-	38.	608.	ò	÷	•0000
250000 2882.1 -24.1 -40.5 21.6 417.9 603.0 270.0 276.0 -276.1 -27.4 42.4 42.4 42.9 42.9 42.9 42.9 42.9 42	2500.0	2000	9	0	Š	٠,	35	676	60	•	•0000
350000 27000	1000 1000	2000	96	2	9	. .	. 52	605		.	• 60000
40000	\$500.0	3000	٠ د د	7	47.	.		603	2	;	•0000°
4500.00 270.00 2	1000	330C	22	91	, c	0.7	-:	509	٠. ا	٥,	0000
550000 2550 - 4500 - 45	\$500.0 257.2 -59.7 -51.0 2.0 - 17.0 25.1 117.0 25.1 110.0 25.2 110		•	3	200	5	• •	000	•	•	50000
550000 252.7 - 47.5 - 47.0 2.0 - 48.4 7 7.0 2.0 - 47.0	55000 258.4 -77.5 -57.5 10.2** 797.4 598.1 119.1 24.1 10000 258.4 -78.6 -62.3 6.1** 77.6 503.9 117.9 25.2 1.0000 247.2 -40.8 241.7 -41.8 20.0 241.7 -41.8 20.0 241.7 -41.8 20.0 241.7 -41.8 20.0 241.7 -41.8 20.0 241.7 -42.7 241.0 241.7 241.8 241.8	4500.	0.	•	53	7.9	97	000	17.	·	0000
252.7	25000	5000		7	57.	2.0	5	298	6	•	.00003
6500.0 252.7 -39.7 -71.0 2.0** 777.2 595.6 5000.0 247.2 -40.3 -71.0 2.0** 777.2 595.7 595.0 250.0 250.4 -42.	6500.0 252.7 -39.7 -71.0 2.0** 777.2 595.2 117.9 25.5 1.0000 247.2 -40.8 1.0000 247.2 -40.8 117.9 25.5 1.0000 241.7 -41.8 1.0000 25.0 117.6 22.4 1.0000 250.0 250.9 -44.0 2.0000 250.2 99.2 25.6 1.0000 250.0 14.0 2.0 1.0000 250.0 14.0 2.0 1.0000 250.0 14.0 2.0 1.0000 250.0 14.0 2.0 1.0000 250.0 14.0 2.0 1.0000 250.0 1.00000 250.0 1.0000 250.0	5500	9	0	r.j	•	• •	965	•	•	-00000
700000 E4107 - 41000	70000	• COO •	25	(A)	-	0	7.	295	•	Š	.0000
7500.0 236.4 - 42.7 7500.0 231.1 - 43.6 5500.0 250.0 - 24.4 5500.0 215.9 - 44.4 5500.0 217.0 - 40.5 1000.0 217.0 - 40.5 1000.0 10000.0 10000.0 10000.0 10000.0 10000.	75000	6203		3			ر م	203	. ·	•	.0000
2500.0 250.9 -44.0 391.0 250.0	1000	0000	•	5				265	•		• 0000%
200000 225.9 144.6 145.0 144.4 145.0 144.4 145.0 144.4 145.0 144.4 145.0 144.4 145.0 144.4 145.0 144.4 145.0 144.4 145.0 144.4 145.0 146.4 145.0 146.4 145.0 146.5 145.0 146.5 145.0	5503-0 231-1 -43.6 1-63.6 1-600 255.9 1-60	7500.	36.	52			57.	591	•	÷	0000
5506.0 225.9 -44.0 350.0 220.9 -44.0 570.0 220.9 -44.0 570.0 220.9 -44.0 570.0 220.9 -44.0 570.0 220.0 220.9 -45.0 570.0 220.0 215.9 -45.0 570.0 220.0 220.0 270.0	ESGCO 225.9 -44.0 735.4 589.2 67.8 25.5 1.5000 9000 225.9 -44.6 735.4 589.2 67.8 26.9 1.5000 9500 215.9 -45.6 87.6 27.5 1.0000 1500 216.2 -45.6 87.6 27.5 1.0000 1500 216.5 -45.6 87.6 32.9 1.0000 1500 27.5 -45.6 87.6 97.9 33.5 1.0000 1500 27.5 -45.6 97.9 33.5 1.0000 1.0000 1500 17.2 -50.7 57.7 57.7 1.0000 1.0000 1500 188.0 -51.1 1.0000 188.0 1.0000 1.0000 1500 183.7 -51.1 1.00000 1.00000 1.00000 1.0000 </td <td>.C003</td> <td>31.</td> <td>£3</td> <td></td> <td></td> <td><u>چ</u>.</td> <td>290</td> <td>ċ</td> <td>,</td> <td>.0000</td>	.C003	31.	£3			<u>چ</u> .	290	ċ	,	.0000
90000 250.9 -44.4 9500.0 215.9 -45.5 6000.0 217.0 -40.5 6000.0 206.2 -47.6 6000.0 201.5 -42.6 1500.0 192.4 -50.5 2007.0 192.4 -50.3 2007.0 188.0 -41.1	90000 220.9 -44.4 26.5 5 736.4 389.2 67.8 26.9 1.0000 250.0 215.9 -45.5 1.0000 215.9 -45.5 1.0000 215.9 -45.5 1.0000 215.9 -45.5 1.0000 215.0 -46.5 1.0000 215.0 -46.5 1.0000 215.0 -47.6 1.0000 216.5 1.0000 216.5 1.0000 216.5 1.0000 197.0 -45.6 1.0000 197.0 -49.5 1.0000 197.0 -49.5 1.0000 197.0 -49.5 1.0000 197.0 -41.1 1.0000 197.0 -41.1 1.0000 197.0 -41.1 1.0000 197.0 -41.1 1.0000 197.0 -41.1 1.0000 197.0	22000	23.	77			4.7	660	•	٠.	.0000
9500.0 215.9 -45.5 726.5 726.4 587.3 587.5 500.0 217.0 -40.5 585.5 726.4 586.4 586.4 586.4 586.4 586.4 586.4 586.4 586.4 586.4 586.4 585.4 586.4	9500.0 215.9 -45.5 1.0000 5000.0 217.0 -40.5 1.0000 5000.0 206.2 -47.6 1.0000 1500.0 206.2 -47.6 1.0000 1500.0 1.0000 1.0000 1500.0 1.0000 1.0000 1500.0 1.0000 1500.0 1.0000 1500.0 1.0000 1500.0 1.0000 1500.0 1.0000 1500.0 1.0000 1500.0 1.0000 1500.0 1.0000 1500.0 1.0000 1500.0 1.0000	6000s	20.	77			35.	. 6 a C	,	è	.0000
CGGGG 21G 746.5 CGGGG 206.2 -47.6 1CGG-7 271.5 -45.6 1SGG-G 197.0 -49.5 CGG-G 192.4 -50.3 2SGG-G 188.9 -51.1	CGDD-0 211.0 -46.5 87.6 57.5 1.0000 C50G-0 206.2 -47.6 32.9 1.0000 1CCD-0 271.5 -45.6 33.5 1.0000 1507.0 197.0 -49.5 36.7 34.1 1.0000 2007.0 192.4 -50.3 37.4 1.0000 250G-0 188.0 -51.1 37.4 1.0000 260D-0 183.7 -52.1 34.2 1.0000	.0055	15.	.¥			۳,	587	٠.	•	.0000
1000.0 206.2 -47.6 112.0 218.5 583. 1100.0 271.6 -45.6 112.0 271.0 583. 112.0 583. 112.0 583. 1120.0 192.4 50.3 500.0 198.0 583. 1120.0 583. 1120.0 583. 1120.0 583.	C500.0 206.2 -47.6 32.9 1.0000 1000.0 201.5 -45.6 33.5 1.0000 1500.0 192.4 -50.3 34.1 1.0000 2000.0 198.0 -51.1 1.000 33.4 1.000 2000.0 188.0 -51.1 295.0 37.4 1.000 2000.0 183.7 -51.1 34.2 1.000	.0000	•	4.0			24.	5 P 6 •	٠,	ċ	. nooo1
1000.0 201.6 -45.6 1500.0 197.0 -49.5 2000.0 192.4 -50.3 2000.0 198.0 -51.1	1000.0 201.6 -45.6 1.0000 1500.0 197.0 -49.5 34.1 1.0000 2000.0 192.4 -55.3 37.4 1.0000 2500.0 188.0 -51.1 5 33.4 1.0000 2600.0 183.7 -52.1 1.0000	0000	90	1-			<u>a:</u>	585	÷	۲,	-0000.
1500.0 192.4 -50.3 560.0 581.0 582. 2500.0 198.0 -51.1	1500-0 197-0 -49.5 54.1 1-0000 200-0 192-4 -59.2 54.1 1-0000 2000-0 192-4 -59.3 57.4 1-0000 2500-0 192-4 -59.3 57.4 1-0000 2500-0 188-0 -51.1 5.0000 2500-0 183.7 -52.1 1-0000	10001		4.5			12.	583	٠,	*	.0000
2000-0 192-4 -50-3 2500-0 188-0 -51-1	2000.0 192.4 -55.3 31.4 1.0000 2500.0 188.0 -51.1 33.4 1.0000 2000.0 183.7 -52.1 34.7 1.0000	1503.	-	63			90	582	•	;	+0000°
-085 C-368 0 -51-1	2506.0 188.0 -51.1 33.4 1.0000 2000.0 183.7 -52.1 34.7 1.0000	2002	,,	S			C)	5 P 1 •	÷		.0000¢
	2000.0 183.7 -52.1 34.1 1.0000	.506.	8	7			, v.) # O •	,•	3	90000
		000	-7				0	. 5	,•	,	00000

** AT LFMST ONE ASSUMED RELATIVE HUMINITY VALUE MAS USED IN THE INTERPOLATION.

STATION ALZ 3 JULY 82 ASCENSION	ALTITUDE 59' 82 30'NO. 84	912.75 FEET MSL 1215 MDT		UPPER AIR 1 254029300 6-20 FABLE-14 CC	s DATA 3084 cont'd		GEODETIC 37.8	C COORDINATES 89927 LAT DEG AGS91 LON DEG
EOME	PRESSURE	TEMPE	REL .HUM.	GM/CHATC	SPEED OF	WIND D	ATA	INDEX
L FEE	MILLIBARS	ES CENTIGR	;	METER	KNOTS	C CK	KNOTS	REFRACTION
3500.	6	5		84.	77.	103.4		90000
* 0003	Š	•		62	76.	,	35.6	9000
450C	.	55		74.	74.	•	è	0000
0	٠,	۲,		60	72.	C · (•	•0000
5500.	m c			90	•	.	N 1	50000
000	• ·			3	• • •	3, C		\00000•
7000	: :	7 m		 	67.	• •	• •	
7500	68	. ~		77	65	•	00	00000
£300°	44.	63		30	66.	-		0000
£500.	۵	64		35.	62.	ċ	•	0000
.0003	17.	65		90	60.	•	•	\$000
950C	40	67		92	59.	٧.	· ·	0000
0000	٠ د د د د د د د د د د د د د د د د د د د	168.0		21.	e) e Gregoria		٠.	•0000
0000	27.	80 0		7.	90	114.0	•	90000
1000	21.	> C		, 80 0	77.	•	• •	
2000	18	7.		200	9 4 7 97 7 47	c	. ~	20000
2500	15.	70		80	54.	ec.	2	0000
2000	12.	5		• 25	55.		:	.0000
2500		167.7		v. c	558.4	10%6	C	00004
* 000 × 7	9 6	,,		2 4			•	
5000		7-22-		•	9 80		٠ ﴿	20000
5500		67		67	59.	. (•	20000
• 0009	÷	-56.6		6,	60	112.0	5.	10000
6530.	•	65		901	6 0.	•	•	٠,
7000	.	1.50		۴,	61	•	•	10000
	•	6;		٠.	• • •	6.11	ė.	٠ (
0000	٠.	Ŝ		ů	61.	•	•	000
67 CC	٠.	ŝ		• •	9 '	•	Ö	.0000
7 C C C	•	3;		٠.	,,	•	•	, 0000
2000	• (^ *· · · · · · · · · · · · · · · · · · ·		•	*		•	
	, r	91		ំក	6	•	٠.	
900	•	4 2		•	C)	• • •	
	• ·	, ;		ٰے •	• a	•	•	. ה ה ה ה ה ה ה ה ה ה ה ה ה ה ה ה ה ה ה
2002	•	1 (a)		117.1	00		25.1	20
62500.0	70.0	6		٠,٠,	0.045	116.7	•	0000
2000		-18.4		•	0		5.92	2000

STATION ALTITUDE 13 JULY 82 ASCENSION NO. 8		3912.75 FEET WSL 1215 MDT 14	T w S L	.	upper AIR 0AIA 2040290084 F-26 TABLE-14 cont'd	oata 84 cont'd		GEODETI 32.	GEODETIC COORDINATES 32.89927 LAT DEG 106.40591 LON DEG
GEOMETRIC Altitude MSL Feet	PRESSURE MILLIBARS		TEMPERATURE AIR DEWPOINT DEGREES CENTIGRADE	REL.HUM. PERCENT	DENSITY GM/LUBIC METER	SPEED OF Sound Knots	WIND DATA DIRECTION S DEGREES(TN) K	TA SPEED KNOTS	INDEX Of Refraction
6	;				8,701	571.9	449.4	25.6	1.000074
6.500.0	000				7	571.1	110,7	24.7	1,0000-3
0.000,79	65.1	1.00-					C	22.9	1.000023
64500.0	63.5	-58.6			20.00		4 V F •	74.4	1.000022
63000.0		-59.1			ט•רטר			- 0	0000
0.008.9		-59.1				220.0	110	2007	330000
6,000,5		-58.7			0-96		15.0	7.22	1,0000
0 0 0 0 0 0 0	47.7	4.8.			9.16	8 570.9	12.0	2.42	L 20000 • L
					010		109.4	25.1	1.0000.1
		6 62			60	572.5	0.0	28.3	1.000020
		30 10 1			98		8.5	31.3	1.000019
0.0000		7 6 6 6			78		75.2	34.8	1.000019
6E500.0		0.01					7.77	14.7	1.000018
69735.0		->4.0			0 1				410000
69500.0	20.	-55.6			۱ ج		•		4 0000
7.000.0		-52.3			77.				N 10000
70500		-51.5			75.	280.0			7.0000
710000	9.94	-50.9			1.02 1.02				0.0000
0.00016		-50.4				3 581.5			20000

GEODETIC COORDINATES 32-89927 LAT DEG 136-40591 LON DEG	4 d	XXO1S	6°S	6.7	3. 5	2.5	7.0	8.4	2.2	15.8	6.5	2.7	6.2	4.9	8.4	8.8	9•6	3.5	6.1	7.5	5.00	5.3	1.2	2.1
ŭ	AIND DATA	DEGREES (TN)										138.7 2												84.9
EVELS 34	REL .HUM.	- E × C E ×	42.	45.	.1.	• 0•	.7.	•97	48.	22.	20.	20.	21.	21.										
MANDATORY LEVELS 2040290084 E-26 TABLE-15	TEMPERATURE P PERSONAL	CENTIGRADE	12.7	0.7	7.7	5.1	C .	-7.6	-12.6	8.72-	-30.3	-31.0	-38	-45.8										
≩ ⊢	TEMP	S	7.93	2.23	17.6	12.	7.8	2.8	-3.2	-6.7	-12.3	-16.2	-22.9	-30.7	-40.3	0.67-	-54.6	-61.8	9.67-	-67.6	-63.1	-59.1	-58.9	-52.6
L MSL	EOPOTENTIAL	FEET	5089.	6834.	8662.	10583.	12668.	14758.	17043.	19502.	22172.	28085	2835% .	₹2006	76169.	41072.	43916.	47097	50728.	55102.	59555	62276.	65455.	9526
STATION ALTITUDE 3912.75 FEET 23 JULY 82 1215 MDT ASCENSION NO. 84	PRESSURE GEOPOTENTIAL	MILLIBARS	0 • ακε	0.00%	0.027	730.0	0.029	0.009	0.025	₽•00.	0°057	0.002	\$50°0	0°00±	0*052	0°00°	175.0	150.0	125.0	130.0	90.08	0.07	0.09	0.05

AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

